

QA12 & 5-QA12

Fire Alarm Control Panel



5-QA12
5 Zone Detector



QA12
10 - 80 Zone Detector

Characteristics

- Alarm verification up to 7 seconds for real fire confirmation and avoid false alarm from environment interference.
- Zone test mode to perform alarm and fault functional test.
- Each zone has a separate disable function.
- Fault indications for wire disconnection, unstable AC power, battery short circuit or disconnection and internal PCB unplug.
- 5-QA12 only up to 5 zones, QA12 could up to 80 zones.



Specifications

Model	5-QA12	QA12
Power	220V AC, 50/60Hz *Others also available	
Battery Capacity	24V/4Ah	
# of heat detectors connected	No limit *Except electronic-type	
# of smoke detectors connected	30/zone *Horing Lih manufactured	
End of Line Resistor	10kΩ *One per zone	
Material	1.2mm steel plate	
Color	Pearl gray *Others also available	
Dimensions (mm) H x W x D	320 x 250 x 100	10 zone : 450 x 330 x 130 20 zone : 550 x 330 x 130 30 zone : 680 x 380 x 150 40 / 50 zone : 950 x 420 x 150 60 ~ 80 zone : 1300 x 420 x 170

Agent In Thailand : U.P.TECH CORPORATION CO.,LTD

28 Soi Rattanathibet 28 Yaek 2 Bangkrasor Muangnonthaburi
Nonthaburi 11000 Thailand

LINE : 0863133492 **Tel** : 02-965-7701-6, 086-355-6781

Email : sales@up-t.com **Email** : admin@up-t.com

Website : www.alarmthailand.com , www.firealarmonline.com

 **HORING LIH INDUSTRIAL CO., LTD.**

4F., No. 18, Lane 327, Chung Shan Road, Sec. 2, Zhonghe District 235, New Taipei City, **Taiwan**

Tel : +886 2 22487599 **Fax** : +886 2 22407752 **Email** : export@horinglih.com **Website** : www.horinglih.com