




# AH-0621

## Photoelectric Smoke Detector

### Characteristics

- Contacts material is highly acid-resistant and rust-resistant.
- Twin-color LED display enables viewer to easily identify the current status of detector.
- Detector is made of high endurance, solid and colorfast Fire-proof plastic.
- The standard detector is 2-wire or 3-wire. For 4-wire type just add one relay output module on 3-wire base. Simple and easy module placement enables wider application and flexible stock control.
- Non-loosening screws on base terminal for easy installation.
- Detector has passed strict EMC test, which greatly eliminates false alarms caused by interference from nearby sources.



### Specifications

Model	AH-0621-2	AH-0621-3	AH-0621-4
Alarm Contact	N/A	N/A	0.8A @30V DC 0.4A @125V AC
Voltage Range	12 ~ 30V DC		
Alarm Current @24V DC 470Ω	50mA	59mA	45mA
Standby Current @24V DC 470Ω	140μA		25~75μA
Sensitivity Setting	Comply to UL 268		
Ambient Temperature	0°C ~ +37.8°C		
Material	Fire-proof plastic		
Dimensions	102mm(Dia.) x 48mm(H)		
Weight	130g	130g	145g
Color	White		

### Effective alert area

Building Height	Area Covered
Under 4M	150 M <sup>2</sup>
4 ~ 20M	75 M <sup>2</sup>

### Order information

AH-0621-2	2-wire
AH-0621-3	3-wire with remote indicator output
AH-0621-4	4-wire with relay output

### Agent In Thailand : U.P.TECH CORPORATION CO.,LTD

28 Soi Rattana Thibet 28 Yaek 2 Bangkrasor Muangnonthaburi Nonthaburi 11000 Thailand

LINE : 0863133492 Tel : 02-965-7701-6, 086-355-6781

Email : sales@up-t.com Email : admin@up-t.com

Website : www.alarmpthailand.com , www.firealarmonline.com

## HORING LIH INDUSTRIAL CO., LTD.

4F., No. 18, Lane 327, Chung Shan Road, Sec. 2, Zhonghe District 235, New Taipei City, Taiwan

Tel : +886 2 22487599 Fax : +886 2 22407752 Email : export@horinglih.com Website : www.horinglih.com