



QA16

Addressable Fire Alarm Control Panel



Characteristics

- Each loop can connect up to 250 addressable devices. Maximum networking are 32 loops and total addressable points are 8000.
- Large LCD screen (40 x 15 lines) allows more events to be displayed on the same screen.
- Loop device can be set up to be temporarily isolated.
- Individual loop module test feature to save time on panel test.
- On-board Self-test feature for simulating alarm output.
- Easy system programming through PC to panel.
- Events log can store up to 2030 events.
- Specification Optional thermal printer that can printout complete panel status.

QA series can be in single or 32 loops network configurations. This system is designed for all applications with advantages of easy installation, fast and precise detection and simple maintenance. Friendly HL Fire Tool software saves your time from programming. Reliable QA series definitely meets your demands for safety.

Specifications

Model	QA16
Power	220V AC 50/60Hz *Others also available
Battery Capacity	24V DC 4Ah
Charging Voltage, Current	26V DC 100~1000mA *With auto adjustment function
Zone Voltage, Current	26.5V DC 340mA
System Capacity	250 devices/1 loop *Expandable for site requirement
Exterior Resistance	Round-trip under 40Ω
Transmitting Method	Digital series transmitting
Accumulation Time	0~40 seconds *Other options available
Main Sound	85dB @1M
Material	1.6mm steel plate
Color	Pearl gray
Dimensions (mm) H x W x D	1~4 loop: 400 x 500 x 130 5~8 loop: 600 x 500 x 150

Agent In Thailand : U.P.TECH CORPORATION CO.,LTD
 28 Soi Rattanathibet 28 Yaek 2 Bangkrasor Muangnonthaburi
 Nonthaburi 11000 Thailand
LINE : 0863133492 **Tel** : 02-965-7701-6, 086-355-6781
Email : sales@up-t.com **Email** : admin@up-t.com
Website : www.alarmpthailand.com , www.firealarmonline.com

 **HORING LIH INDUSTRIAL CO., LTD.**

4F., No. 18, Lane 327, Chung Shan Road, Sec. 2, Zhonghe District 235, New Taipei City, **Taiwan**
Tel : +886 2 22487599 **Fax** : +886 2 22407752 **Email** : export@horinglih.com **Website** : www.horinglih.com